



X⁵Pro

The smart profiler package that maximizes investment with smart optimization and proactive oven health monitoring capability



X5 Pro

X⁵Pro™ Advantages

- Robust Hardware
- Smart Oven Setup Software
- Includes KIC HeatMap™ Option
- Compatible with KIC Ecosystem
- 2 Year Warranty
- 24 Hour World Class Customer Support

Pro Capabilities

- Transforms underused profilers into highly productive monitoring tools
- Real-time visualization of each zone's performance vs a reference condition
- Identifies intermittent thermal drifts that may not be visible during isolated profile checks
- Integrated Navigator Power™ optimization. Powerful search engine identifies optimum recipe setup
- PWI – Instant process analysis with a single number
- Unique process specifications for each thermocouple

Additional Standard Features


- Intuitive TAS (Thermal Analysis System) software
- Fast and accurate manual profiling
- Single screen overview
 - Profile graph
 - Metrics (slopes, reflow time, peak)
 - Oven settings
 - Suggested optimal settings
- Solder paste specification library
- SPC charting - Automatic Cpk calculations

Optional Smart Features – AI, Data Analytics, Automated Outputs

- ***NEW* Common Recipe Finder™** for efficient production changeover and improved Overall Equipment Effectiveness
- Auto-Focus Power™ - automated NPI oven recipe creation
- Sweet Spot Process Development for better process results
- TC mapping for report/audit documentation
- External data outputs
- Audible light tower for out of spec conditions

Hardware and Built-In Conveniences

- Robust and durable design
- Operates on three AAA batteries or USB powered when connected to PC
- 7, 9, and 12 channel configurations
- Push button on/off with LED indicator
- Variety of available thermal shields



X⁵Pro

X⁵Profiler with HeatMap™

X⁵ Profiler Specifications

Accuracy:
 -150°C to 0°C ±(1.1°C = 1.1%)
 0°C to 500°C ±1.1°C
 500°C to 1050°C ±(1.1°C = 0.3%)
 Resolution:0.1°C
 Internal Operating Temp: ..0°C to 85°C
 Sample Rate:0.002 to 10 readings/second
 Max Data Points:224,640
 Temperature Range:-150°C to 1050°C
 PC Connection:USB 2.0 (Std-A/Mini-B)
 Power:(3) AAA batteries
 (USB power when connected to PC)
 Thermocouple Compatibility: Type K, Standard
 Dimensions (L x W x H mm):
 7-channel:202.0 x 60.0 x 17.0
 9- channel:202.0 x 75.0 x 17.0
 12-channel:208.0 x 98.0 x 17.0

X ⁵ Pro Kit Contents	
X ⁵ Smart Profiler	Gloves
HeatMap Probe - 1 TC per Zone* (15 TC Maximum)	Scissors
HeatMap Mounting Hardware	Software/Manuals/Hardware Guides on USB Thumb Drive
HeatMap Self-Installation** Guide	USB Software Protection Dongle
2 USB Cables (A-Male/Mini-B)	Getting Started Guide for Profiler and HeatMap
Thermal Shield*	Calibration Certificate
Thermocouples**	Carrying Case

* These items may vary according to specific models/configuration ordered.
 ** KIC Installation and Training available for HeatMap. Contact KIC for details.

HeatMap Probe Specifications

Accuracy: ± 1.1°C
 Thermocouples: Type K
 Maximum Temperature: ...450°C

X⁵ WITH THERMAL SHIELD DIMENSIONS TEMPERATURE DURATION (MINUTES)

Models	Length x Width x Height	150°C	200°C	250°C	300°C	350°C	400°C
7 CH Single Layer Cool Touch	303 x 75 x 24	17.5	12.0	9.0	7.7	6.5	
7 CH Triple Layer Cool Touch	303 x 81 x 30	26.8	17.6	13.4	11.1	9.7	
7 CH HT-400 Stainless Steel *	304 x 78 x 29	24.9	17.6	14.0	11.5	10.1	9.2
9 CH Single Layer Cool Touch	313 x 91 x 24	18.1	13.1	10.1	8.4	6.7	
9 CH Triple Layer Cool Touch	313 x 96 x 30	26.3	17.1	13.4	10.9	9.4	
9 CH HT-400 Stainless Steel *	304 x 93 x 29	24.9	17.6	14.0	11.5	10.1	9.2
12 CH Single Layer Cool Touch	325 x 115 x 24	17.7	12.0	8.9	7.4	6.1	
12 CH Triple Layer Cool Touch	325 x 120 x 30	24.6	17.8	13.8	11.7	9.9	
12 CH HT-400 Stainless Steel *	310 x 117 x 29	24.9	17.6	14.0	11.5	10.1	9.2

*Compatible with Datalogger mode only



Corporate Headquarters

16120 West Bernardo Drive • San Diego, CA 92127 USA
 +1(858)673-6050 Phone • +1(858)673-0085 FAX
 sales@kicmail.com • tech@kicmail.com

European Regional Office

europe.sales@kicmail.com • europe.tech@kicmail.com

Asian Regional Office

asia.sales@kicmail.com • asia.tech@kicmail.com
 kicthermal.com kic.cn

Minimum System Requirements

Dual Core / 1 GHz Processor PC with 2 GB RAM
 2 GB available storage
 Video 1024 x 768 resolution / 16-bit
 1 available USB port (for data download or Smart Dock)
 1 available USB port (for software protection dongle)
 Visit our website at <https://kicthermal.com/support/os-compatibility-chart/> for product compatibility with Windows operating systems.



All KIC products are designed to give maximum value and fast payback by streamlining your thermal process. Investment in a KIC product is a step toward total process control and quality management. All KIC products come with a no questions asked, 30-day money back guarantee.

Copyright © KIC. All rights reserved. Patents pending. Specifications subject to change without notice. KIC and KIC Thermal Profiling are divisions of and registered trademarks and tradenames of Embedded Designs Inc. RPI i4.0, SPS, SRA, SmartDock, X5, KIC Start2, K2, Vision2, Navigator Power, Auto-Focus Power, KIC RPM, KIC Carrier, Wave Surfer, RPI, Process Window Index, PWI, HeatMap and the KIC logo are trademarks or registered trademarks of KIC. All other trademarks and tradenames are the property of their respective holders.